## PNHLR/G Horizontal Rotary Laser, pendulum leveling (SKU no. 205-PNHLR and 205-PNHLG)

## Features

- Choose between red or green beam pendulum laser
- Very rugged against temperature variations
- Stable and robust leveling technique
- Inexpensive and reliable rotary laser
- Red beam only: Horizontal scanning functions ideal for composition floors and interior finishing. Green beam: even without scanning very well visible.

Technical Da	

Leveling accuracy  $\pm 3 \text{ mm/30 m}$ 

Leveling range  $\pm 4^{\circ}$ 

Working range Up to 500 m radius with

detector

Laser Class 2 (red: 635 nm, green: 520 nm)
Power supply Lithium-lon batteries (20 h)

Operating temperature -10°C to +45°C

IP protection IP55

 Rotary speed
 300, 600, 1000 rpm

 Dimensions
 215 mm (length) x

 150 mm (width) x

156 mm (height)

Weight 2.0 kg



For all types of construction work interior and leveling, e.g., laying composition floors, depth control for excavators, fundaments, walls, height control, landscaping

## Scope of delivery

- Rotary Laser PNHLR (red) or PNHLG (green)
- Rechargeable Lihtium-Ion battery and charger
- Target
- Laser glasses
- Transportation case
- Instruction manual

Get an optimum working range with our universal detector PNLUD14 (page 8) which receives rotary and line laser beams! More benefit for your customers: One detector - both laser types.

## Service

Service directly at proNIVO! Our qualified service center performs repairs and maintenance of this instruments. You save cost and time.

We offer tripods, rods and other accessories. Have a look in our tripod catalog and ask for your offer!







Strada IACOB NEGRUZZI nr. 44, 011094, Bucuresti-1 (+40)722 620 305 e-mail:topotrade@yahoo.com www.topotrade.ro